

HSK – Ihr Partner für Kunststoffschweiß- und Biegetechnik
HSK – Your partner for plastic welding – and bending technology

Hand welding extruder HSK40 /HSK40 E



BASIC EXTRUDER

- Extrusion welding from PEHD, PP, PVDF and PVC*
 - rod feeding, no additional gearing
 - Cold start protection
 - Rod diameter 3, 4 and 5 mm
 - 1 pce nozzle blank included
- *PVC with special screw

TECHNICAL DATA

Output	3.8 kg/h (with PEHD rod 5 mm)
Heating extruder	with air heater 2200 W
Drive	1.100 W
Air requirement	300 l/min. (not version "E")
Voltage	230 V / 50Hz
Weight	8 kg
Guarantee	screw and cylinder 24 months

HSK40 E (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 2200 W

ADDITIONAL EQUIPMENT

- | | | |
|----------------------|----------------------------|---------------|
| ▪ Welding nozzles | Extruder nozzle preheating | Angle adaptor |
| ▪ Transportation box | Prolongation | Air compactor |
| ▪ Welding rod | Widen | |

Technical execution subject to modifications